

+ MATERIAL SAFETY DATA SHEET +

SEA MUD

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: Diversity Technologies Corp. DATE: October 22, 2015

8750 – 53rd Ave. PHONE: **780-440-4923 Edmonton, AB T6E 5G2** FAX: **780-469-1899**

PRODUCT NAME: SEA MUD (formerly Salt Gel)

PRODUCT USE: Oilwell drilling fluid additive.

CHEMICAL FAMILY: Sepiolite clay CAS #: 63800-37-3

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: D2A

WORKPLACE HAZARD: Potential carcinogen; contains crystalline silica

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG

TDG CLASSIFICATION: Not applicable UN NUMBER (PIN): Not applicable PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: □ EYE CONTACT □ SKIN CONTACT ☑ INHALATION □ INGESTION

EYE CONTACT: Mechanical irritant.

SKIN CONTACT: Possible drying resulting in dermatitis.

INGESTION: No adverse effect expected.

INHALATION: Inhalation may cause irritation of the nose, throat and respiratory

passages. Long-term inhalation may cause silicosis, a progressive, disabling and, sometimes, fatal lung disease. Chronic inhalation exposure to crystalline silica quartz has been observed to cause lymph

node effects, kidney effects and auto-immune disease.

CARCINOGENICITY: Crystalline silica when inhaled in the form of quartz or crystobalite from

occupational sources is carcinogenic to humans: The IARC has concluded that this chemical is carcinogenic to humans (Group 1). The ACGIH has designated this chemical as a suspected human carcinogen (A2). The US

NTP has listed this chemical as a known human carcinogen.



+ MATERIAL SAFETY DATA SHEET +

SEA MUD

TERATOGENICITY: No information available. REPRODUCTIVE TOXICITY: No information available.

MUTAGENICITY: Crystalline silica has been shown to cause mutagenic effects in human

cells in-vitro.

SYNERGISTIC PRODUCTS: No information available.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: If irritation occurs, or at end of shift, wash thoroughly with soap and

water. If irritation persists, obtain medical attention.

EYE CONTACT: Flush with gently flowing warm water until particles are removed. If

irritation persists, obtain medical attention.

INGESTION: No adverse effects expected. If symptoms develop, or if large amounts

are ingested, obtain medical attention.

INHALATION: Move to area free from dust. Apply oxygen or artificial respiration if

required. If breathing difficulties or distress continues, obtain medical

attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR: Grey or tan powder; earthy odour when wet

SPECIFIC GRAVITY: 1.9 - 2.4 BOILING POINT (°C): >537

MELTING POINT (°C): Not applicable

SOLUBILITY IN WATER: Insoluble pH: 4 – 8

PERCENT VOLATILE BY VOLUME:

EVAPORATION RATE:

VAPOUR PRESSURE (mmHg):

VAPOUR DENSITY (air = 1):

BULK DENSITY:

Not applicable

Not applicable

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Non flammable

FLAMMABLE LIMITS: None

EXTINGUISHING MEDIA: Use media suitable for packaging and surrounding

materials.

SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus required for fire-

fighting personnel. Becomes very slippery when wet.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

HAZARDOUS COMBUSTION PRODUCTS: No information available.



+ MATERIAL SAFETY DATA SHEET +

SEA MUD

SECTION VII: REACTIVITY DATA

STABILITY:

STABLE

UNSTABLE

INCOMPATIBILITY (CONDITIONS TO AVOID): None known. CONDITIONS OF REACTIVITY: Not known. HAZARDOUS DECOMPOSITION PRODUCTS: Not known.

HAZARDOUS POLYMERIZATION:
☑ WILL NOT OCCUR
☐ MAY OCCUR

SECTION VIII: PREVENTIVE MEASURES

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NIOSH/MESA approved respirators for silica bearing

dust.

VENTILATION: Use local exhaust ventilation, process enclosure or

other engineering controls to maintain airborne levels

below PEL's/TLV's.

PROTECTIVE GLOVES: Generally not necessary; personal preference. EYE PROTECTION: Suggest safety glasses or goggles be worn.

OTHER PROTECTIVE EQUIPMENT (SPECIFY): Ensure eye wash station and emergency shower are

available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid breathing dust; wear an approved respirator. Practice reasonable caution and personal cleanliness. Avoid eye contact. Use dustless system for handling, storage, and clean up. Do not permit dust to collect on walls, floors, sills, ledges, machinery, or equipment. Launder contaminated clothing before reuse. Material may become very slippery when wet. Store in a cool, dry area. Empty packaging contains residual hazardous material and should be handled as if full.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Use suitable protective equipment including respiratory protection. Avoid creating dust cloud, vacuum if possible. Collect uncontaminated material for repackaging. Collect contaminated material in an approved container for disposal. Spilled material may become very slippery when wet.

WASTE DISPOSAL METHOD

Dispose of in accordance with federal, provincial and local regulations. Material can be land filled in most areas; check with local operator. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal.



🗕 🛨 MATERIAL SAFETY DATA SHEET 🛨

SEA MUD

SECTION IX: PREPARATION

The information contains herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED: October 22, 2015
SUPERSEDES: October 22, 2012
BY: Regulatory Affairs
PHONE: 780-440-4923